

GOLDBERG BROTHERS BARN DOOR HARDWARE BARN DOOR SIZING TABLE



STAINLESS STEEL SERIES SINGLE-DOOR CONFIGURATIONS

- The door should be at least as tall as the height of the finished opening.
- The door should be at least 1" wider than the finished opening to allow an overlap of at least ½" on each side when closed.
- The net* track length should be double the door width minus ½" or 1" in order to keep the bottom edge of the door engaged with the door guide on the floor. If necessary, you can place a special order for a track longer than you need and have it custom-cut at our factory.

Use the table below to match the recommended door panel width with the corresponding maximum opening width and track length. The column on the right indicates the minimum hardware required, including the catalog number of the corresponding track in our Stainless Steel Series product line.

Any track more than 8' long can be substituted with two or more shorter tracks, plus a wall mounting kit and a track connecting plate for each additional track. This substitution may reduce the overall expense, due to the potentially high cost of shipping long parcels.

door width	maximum finished opening width	net* track length	minimum Stainless Steel Series hardware required†
1′6″	17"	35½"	 any Stainless Steel Series hardware set track 6005T4 with custom cut to 35½"
1′8″	19"	39½"	 any Stainless Steel Series hardware set track 6005T4 with custom cut to 39½"
2′0″	23"	47½"	any Stainless Steel Series hardware settrack 6005T4
2′4″	27"	55½"	 any Stainless Steel Series hardware set track 6005T5 with custom cut to 55½"
2′6″	29"	59½"	any Stainless Steel Series hardware settrack 6005T5
2′8″	31"	63½"	any Stainless Steel Series hardware settrack 6005T54
2′10″	33"	67½"	 any Stainless Steel Series hardware set track 6005T6 with custom cut to 67½"
3′0″	35"	71½"	any Stainless Steel Series hardware settrack 6005T6
3′6″	41"	83½"	any Stainless Steel Series hardware settrack 6005T7
4′0″	47"	95½"	any Stainless Steel Series hardware settrack 6005T8

TABLE CONTINUES ON NEXT PAGE

1 barn door hardware set, 1 track = 2× the door width -½"

6005IG-SDST_01 0723

^{*}For correct fit and performance, we make our Stainless Steel Series tracks ½" shorter than their nominal length. For example, a 6005T4 track has a nominal length of 4', but a net length of 3'11½". This helps keep the door properly positioned above the door guide when using the most common door sizes.

[†]Some custom installations may require additional or different items not listed. Optional accessories such as door pulls and Soft Stop are sold separately.

STAINLESS STEEL SERIES SINGLE-DOOR CONFIGURATIONS (continued)

door width	maximum finished opening width	net* track length	minimum Stainless Steel Series hardware required†
5′0″	58½"	119"	 any Stainless Steel Series hardware set two tracks 6005T5 (combined 119" net*) one wall mounting kit one track connecting plate 6005C
	59"	119½"	 any Stainless Steel Series hardware set track 6005T100 with custom cut to 119½"
6′0″	70½"	143"	 any Stainless Steel Series hardware set two tracks 6005T6 (combined 143" net*) one wall mounting kit one track connecting plate 6005C
	71"	143½"	 any Stainless Steel Series hardware set track 6005T160 with custom cut to 143½"
7′0″	70½"	167"	 any Stainless Steel Series hardware set two tracks 6005T7 (combined 167" net*) one wall mounting kit one track connecting plate 6005C
	71"	167½"	 any Stainless Steel Series hardware set track 6005T160 with custom cut to 167½"
8'0"	94½"	191"	 any Stainless Steel Series hardware set two tracks 6005T8 (combined 191" net*) one wall mounting kit one track connecting plate 6005C
	95"	191½"	 any Stainless Steel Series hardware set track 6005T160 with custom cut to 191½"

1 barn door hardware set, 1 to 3 tracks = $2 \times$ the door width - $\frac{1}{2}$ " or -1", track connecting plate(s), extra wall mount kit(s)

^{*}For correct fit and performance, we make our Stainless Steel Series tracks 1/2" shorter than their nominal length. For example, a 6005T4 track has a nominal length of 4', but a net length of 3'11½". This helps keep the door properly positioned above the door guide when using the most common door sizes.

[†]Some custom installations may require additional or different items not listed. Optional accessories such as door pulls and Soft Stop are sold separately.